


10G BASE-T PoE ++ TRANSFORMER MODULES

Ruggedized



- ⦿ Compliant with IEEE 802.3 standards
- ⦿ OCL 120µH MIN with 27mA DC bias, at 100KHz, 100mV
- ⦿ Current Rating: 900mA Max per pair
- ⦿ Operating Temperature:
 - 10GB-6013: -40°C to +85°C
 - 10GB-6013X: -55°C to +125°C
- ⦿ Storage Temperature: -55°C to +125°C
- ⦿ Dielectric Withstanding Voltage (DWW): 1500Vrms
- ⦿ Epoxy encapsulated package
- ⦿ Terminal Finish: Sn63/Pb37 (Pure tin for RoHS version)
- ⦿ Moisture Sensitivity Level: 3

Electrical Specifications @ 25°C

Part Number	Insertion Loss (dB MAX)					Return Loss (dB MIN)					Crosstalk (dB MIN)				DM to CM Rejection (dB MIN)		
	100 KHz	1 MHz	300 MHz	400 MHz	500 MHz	1 MHz	100 MHz	300 MHz	400 MHz	500 MHz	1 MHz	100 MHz	400 MHz	500 MHz	1 MHz	250 MHz	500 MHz
10GB-6013	3	1.2	1.2	3	3	22	18	12	10	8	40	37	30	25	40	30	22
10GB-6013X	3	1.2	1.2	3	3	22	18	12	10	8	40	37	30	25	40	30	22

NOTES:






1. Add suffix "NL" for RoHS compliant version; i.e. 10GB-6013 becomes 10GB-6013NL.
2. For Tape & Reel packaging, add "T" suffix at the end of the part number: i.e. 10GB-6013NLT.

Mechanicals


Electrical Schematics

10GB-6013 / 10GB-6013X

Dimensions: inch [mm]
Tolerance (unless otherwise specified): ±0.010 [0.25]



LEGEND



Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2023. iNRCORE, LLC. All rights reserved.

M566.A (8JUN23)

Recommended Reflow Profile (Based on J-STD-020D)



T_{SMIN} (°C)	T_{SMAX} (°C)	T_L (°C)	T_P (°C MAX)	t_s (s)	t_L (s)	t_p (s MAX)	Ramp-up rate (T_L to T_P)	Ramp-down rate (T_P to T_L)	Time 25°C to peak temperature (s MAX)
Tin/Lead Profile									
100	150	183	220	60 - 120	60 - 150	20	3°C/s MAX	6°C/s MAX	360
Non-Lead Profile									
150	200	217	245	60 - 120	60 - 150	30	3°C/s MAX	6°C/s MAX	480

NOTES:

1. All temperatures measured on the package leads.
2. Maximum number of reflow cycles not to exceed 2.
3. Reflow cycle applies only to surface mount parts.

