

10/100BASE - TX SINGLE PORT TRANSFORMER MODULE

Ruggedized

- Compliant with IEEE 802.3 standards
- 350 μ H OCL with 8mA DC bias
- Operating Temperature:
 - 100B-1022: -40°C to +85°C
 - 100B-1022X: -55°C to +125°C
- Dielectric Withstanding Voltage (DWV): 1500 Vrms
- Lead Finish: Sn63Pb37
- Moisture Sensitivity Level: 3

Electrical Specifications @ 25°C

Part Number	Insertion Loss (dB MAX)				Return Loss (dB MIN)					Crosstalk (dB MIN)				DM to CM Rejection Ratio (dB MIN)			
	1 MHz	30 MHz	60 MHz	100 MHz	5 MHz	30 MHz	50 MHz	60 MHz	80 MHz	16 MHz	30 MHz	60 MHz	100 MHz	5 MHz	30 MHz	60 MHz	100 MHz
100B-1022	1.0	1.0	1.0	1.0	20	20	14	14	12	48	45	40	35	42	37	32	32
100B-1022X	1.0	1.0	1.0	1.0	20	20	14	12	12	48	45	40	35	42	37	32	32

NOTES:



- Add suffix "NL" for RoHS compliant version; i.e. 100B-1001 becomes **100B-1022NL**. NL parts have 100% SN Lead Finish (MSL:3)
- For Tape & Reel packaging, add "T" suffix at the end of the part number: i.e. **100B-1022XNLT**.

Mechanicals


Electrical Schematics

100B-1022 / 100B-1022X

Dimensions: inch [mm]
Tolerance (unless otherwise specified): ± 0.010 [0.25]




LEGEND



10/100BASE - TX SINGLE PORT
TRANSFORMER MODULE

Ruggedized

Recommended Reflow Profile (Based on J-STD-020D)



T_{SMIN} (°C)	T_{SMAX} (°C)	T_L (°C)	T_P (°C MAX)	t_s (s)	t_L (s)	t_p (s MAX)	Ramp-up rate (T_L to T_P)	Ramp-down rate (T_P to T_L)	Time 25°C to peak temperature (s MAX)
Tin/Lead Profile									
100	150	183	220	60 - 120	60 - 150	20	3°C/s MAX	6°C/s MAX	360
Non-Lead Profile									
150	200	217	245	60 - 120	60 - 150	30	3°C/s MAX	6°C/s MAX	480

NOTES:

1. All temperatures measured on the package leads.
2. Maximum number of reflow cycles not to exceed 2.



iNRCORE, LLC
311 Sinclair Road, Bristol, PA 19007-6812 USA
Tel: +1.215.781.6400 Fax: +1.215.781.6430

www.iNRCORE.com

M196.G (04AUG25)

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2025. iNRCORE, LLC. All rights reserved.