

10/100 BASE-T SINGLE PORT
TRANSFORMER MODULE

Industrial Grade

- Compliant with IEEE 802.3 standards
- 350μH OCL with 8mA D.C.bias at 100KHz, 100mV
- Dielectric Withstanding Voltage (DWV): 1500 Vrms
- Operating Temperature: -40°C to +85°C
- Lead Finish: Pure Tin
- Moisture Sensitivity Level: 1

Electrical Specifications @ 25°C															
Part Number	Insertion Loss (dB MAX)				Return Loss (dB MIN)					Crosstalk (dB MIN)			DM to CM Rejection Ratio (dB MIN)		
	0.10 MHz	30 MHz	60 MHz	100 MHz	5 MHz	30 MHz	50 MHz	60 MHz	80 MHz	30 MHz	60 MHz	80 MHz	30 MHz	60 MHz	100 MHz
R1003NL	1.0	1.0	1.0	1.0	18	16	12	11	10	45	40	35	42	37	32

NOTES:

- For Tape & Reel packaging, add "T" suffix at the end of the part number: i.e. R1003NLT.
- Country of Origin: China

R1003NL

Mechanicals

Electrical Schematics

Dimensions: inch [mm]
Tolerance (unless otherwise specified): ±0.010 [0.25]

SUGGESTED PAD LAYOUT (REFERENCE ONLY)

TRANSMIT

RECEIVE

LEGEND

CH I P S I D E

ME D I A S I D E

Td

Tx

Rd

Rx


All channels are in phase between input and output



10/100 BASE-T SINGLE PORT
TRANSFORMER MODULE

Industrial Grade

Recommended Reflow Profile (Based on J-STD-020D)



T_{SMIN} (°C)	T_{SMAX} (°C)	T_L (°C)	T_P (°C MAX)	t_s (s)	t_L (s)	t_p (s MAX)	Ramp-up rate (T_L to T_P)	Ramp-down rate (T_P to T_L)	Time 25°C to peak temperature (s MAX)
Non-Lead Profile									
150	200	217	245	60 - 120	60 - 150	30	3°C/s MAX	6°C/s MAX	480

NOTES:

1. All temperatures measured on the package leads.
2. Maximum number of reflow cycles not to exceed 2.



iNRCORE, LLC
311 Sinclair Road, Bristol, PA 19007-6812 USA
Tel: +1.215.781.6400 Fax: +1.215.781.6430

www.iNRCORE.com

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2025. iNRCORE, LLC. All rights reserved.

N001.A (02JUL25)