1000BASE-T PoE/PoE+/PoE++ SINGLE&DUAL TRANSFORMER

Ruggedized

iNRCORE FAMILY OF BRANDS

- Compliant with IEEE 802.3 standards
- Inductance (OCL):
  - 1000B-5009: 350uH with 18mA DC bias
  - 1000B-5060: 250uH with 36mA DC bias
  - 1000B-5061: 250uH with 27mA DC bias
  - 1000B-5062: 250uH with 36mA DC bias
- Operating temperature:
  - Normal: -40°C to +85°C
  - "X" Suffix: -55°C to +125°C
- Dielectric Withstanding Voltage (DWV):1500Vrms MAX
- Lead finish: Sn63Pb37 for leaded version
- Moisture Sensitivity Level: 3

Design Specifications

Part Number	Power (W Max)	Port	Current Rating Per pair (mA Max)	Package	Max Height (inch Max)
1000B-5059(X)	30	Single	600mA	24Pin	0.265
1000B-5060(X)	60	Single	1200mA	24Pin	0.410
1000B-5061(X)	90 (4-Pair)	Single	900mA	24Pin	0.410
1000B-5062(X)	60	Dual	1200mA	48Pin	0.295

Electrical Specifications @ 25°C

Part Number	Insertion Loss (dB Max)				Return Loss (dB Min)			Crosstalk (dB Min)				DM to CM Rejection Ratio (dB Min)		
	0.1 MHz	30 MHz	60 MHz	100 MHz	30 MHz	60 MHz	80 MHz	1 MHz	30 MHz	60 MHz	100 MHz	30 MHz	60 MHz	100 MHz
1000B-5059	1.2	1.2	1.2	1.2	18	14	12	50	43	37	33	43	37	33
1000B-5059X	1.2	1.2	1.2	1.2	18	14	12	50	43	37	33	43	37	33
1000B-5060	1.2	1.2	1.2	1.2	18	12	10	50	43	37	33	43	37	33
1000B-5060X	1.2	1.2	1.2	1.2	18	12	10	50	43	37	33	43	37	33
1000B-5061	1.2	1.2	1.2	1.2	18	12	10	50	43	37	33	43	37	33
1000B-5061X	1.2	1.2	1.2	1.2	18	12	10	50	43	37	33	43	37	33
1000B-5062	1.2	1.2	1.2	1.2	18	12	10	50	43	37	33	43	37	33
1000B-5062X	1.2	1.2	1.2	1.2	18	12	10	50	43	37	33	43	37	33


Notes: 1. Add suffix "NL" for RoHS compliant i.e. 100B-1059 becomes 100B-1059NL. NL parts have 100% SN Lead Finish.
2. Add suffix "T" to part number for Tape & Reel package (ie: 1000B-5059XNLT).

Mechanicals

1000B-5059(X)

Dimensions: inch [mm]

Tolerance (unless otherwise specified): ±0.010 [0.25]




iNRCORE, LLC
311 Sinclair Road, Bristol, PA 19007-6812 USA
Tel: +1.215.781.6400 Fax: +1.215.781.6430

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein maybe trademarks or registered trademarks of their respective owners. © Copyright, 2026. iNRCORE, LLC. All rights reserved.

Mechanicals

1000B-5061(X) /60(X)


Dimensions: inch [mm]
Tolerance (unless otherwise specified): ±0.010 [0.25]



Mechanicals

1000B-5062(X)

Dimensions: inch [mm]
Tolerance (unless otherwise specified): ±0.010 [0.25]




iNRCORE, LLC
311 Sinclair Road, Bristol, PA 19007-6812 USA
Tel: +1.215.781.6400 Fax: +1.215.781.6430

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2026. iNRCORE, LLC. All rights reserved.

Electrical Schematics

1000B-5059(X)/60(X)/61(X)





iNRCORE, LLC
311 Sinclair Road, Bristol, PA 19007-6812 USA
Tel: +1.215.781.6400 Fax: +1.215.781.6430

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein maybe trademarks or registered trademarks of their respective owners. © Copyright, 2026. iNRCORE, LLC. All rights reserved.

Electrical Schematics

1000B-5062(X)






ALL CHANNELS ARE IN PHASE BETWEEN INPUT AND OUTPUT

iNRCORE, LLC
311 Sinclair Road, Bristol, PA 19007-6812 USA
Tel: +1.215.781.6400 Fax: +1.215.781.6430

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2026. iNRCORE, LLC. All rights reserved.

Recommended Reflow Profile (Based on J-STD-020F)



T_{SMIN} (°C)	T_{SMAX} (°C)	T_L (°C)	T_P (°C MAX)	t_S (s)	t_L (s)	t_P (s MAX)	Ramp-up rate (T_L to T_P)	Ramp-down rate (T_P to T_L)	Time 25°C to peak temperature (s MAX)
Tin/Lead Profile									
100	150	183	220	60-120	60-150	20	3°C/s MAX	6°C/s MAX	360
Non-Lead Profile									
150	200	217	245	60-120	60-150	30	3°C/s MAX	6°C/s MAX	480

Notes:

1. All temperatures measured on the package leads.
2. Maximum number of reflow cycles not to exceed 2.

For More Information

iNRCORE,LLC
311 Sinclair Road Bristol,
PA 19007-6812 U.S.A
Tel: + 1.215.781.6400
Fax: +1.215.7816430

Dongguan iNRCORE Co. Ltd
No.7 An Li Road
Changan Town, Dongguan City, China
Tel: +0769 8165 9962

Global Sales Representatives and locations:
http://www.inrcore.com

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein maybe trademarks or registered trademarks of their respective owners. © Copyright, 2026. iNRCORE, LLC. All rights reserved.